

## NOTE: REFER TO

WINDOW HEAD: SSETB-DP2SU032

WINDOW JAMB: SSETB-DP2SU042-44

COMPRESSIBLE BACKER ROD AND  
SILICONE SEALANT AROUND FRAME

PREMANUFACTURED  
THERMALLY BROKEN  
ALUMINUM WINDOW ASSEMBLY

SPRAY APPLIED FOAM INSULATING  
AIR SEAL AROUND FRAME

PREFINISHED ALUMINUM  
SILL c/w END DAMS

COMPRESSIBLE BACKER ROD  
AND SILICONE SEALANT

THIN-CLAD CALCIUM SILICATE BRICK,  
MVIS™ THIN BRICK MORTAR -  
POLYMER FORTIFIED,  
PROGUARD DP® INSULATED CONCRETE  
BOARD PANEL - DOUBLE DRAINAGE  
PLANE (THICKNESS DEPENDENT ON  
REQUIRED R-VALUE),  
MVIS™ AIR & WATER BARRIER or  
WATERARMOR® AWB,  
EXTERIOR SHEATHING,  
STEEL STUD WALL,  
VAPOR BARRIER (LOCATION  
DEPENDENT ON CLIMATE ZONE),  
GYPSUM WALLBOARD

MVIS™ POINTING MORTAR

## ARCHITECT NOTE:

- DETAIL FOR SUPPORTED  
PROGUARD DP® - DOUBLE  
DRAINAGE PLANE PANELS.
- ENGINEER OF RECORD TO SELECT  
PROGUARD DP® SCREW SPACING  
USING NTA REPORT TRIG030116-28.

WATERPROOFING  
TRANSITION MATERIAL

ATTACH PROGUARD  
DP® PANELS WITH  
SILVER C APPROVED  
SCREWS THROUGH  
TO STUDS (TYPICAL)



**ARRISCRAFT · CADD**

TITLE:

ALUMINUM WINDOW SILL -  
DEEP RECESSED WINDOW

DETAIL No:

SSETB - DP2S

**U026**

DATE DRAWN:

02 Mar 2022

SCALE:

1-1/2"=1'-0"

DRAWN BY:

TRI