

THIN-CLAD CALCIUM SILICATE BRICK,  
 MVIS™ THIN BRICK MORTAR -  
 POLYMER FORTIFIED,  
 PROGUARD DP® INSULATED CONCRETE  
 BOARD PANEL - DOUBLE DRAINAGE  
 PLANE (THICKNESS DEPENDENT ON  
 REQUIRED R-VALUE),  
 MVIS™ AIR & WATER BARRIER or  
 WATERARMOR® AWB,  
 EXTERIOR SHEATHING,  
 STEEL STUD WALL,  
 VAPOR BARRIER (LOCATION  
 DEPENDENT ON CLIMATE ZONE),  
 GYPSUM WALLBOARD

## ARCHITECT NOTE:

- DETAIL FOR SUPPORTED PROGUARD DP® - DOUBLE DRAINAGE PLANE PANELS.
- ENGINEER OF RECORD TO SELECT PROGUARD DP® SCREW SPACING USING NTA REPORT TRIG030116-28.

INSULATION CHAMFERED AT TOP AND  
 BOTTOM OF PANEL EDGES TO ALLOW  
 FOR CONTINUOUS DRAINAGE

1'-0" x 8'-0" PROGUARD DP® BASE WEEP  
 PANEL - DOUBLE DRAINAGE PLANE AT  
 ALL FLASHING LOCATIONS

OVERLAP AIR / MOISTURE BARRIER OVER  
 FLASHING MEMBRANE

FLASHING MEMBRANE  
 ADHERED TO SUBSTRATE

COMPRESSIBLE BACKER ROD  
 AND SILICONE SEALANT

PREMOLDED EXPANSION JOINT FILLER

PARGING

ATTACH PROGUARD DP® PANELS  
 WITH SILVER C APPROVED SCREWS  
 THROUGH TO STUDS (TYPICAL)

3" MAX.  
 3" MAX.

TAPE JOINT WITH ALKALI-RESISTANT  
 MESH TAPE AND MUD JOINT WITH  
 MVIS™ THIN BRICK MORTAR

MVIS™ POINTING MORTAR

COMPRESSIBLE BACKER ROD  
 AND SILICONE SEALANT w/  
 WEEP HOLES @ 8" o.c.

PREFINISHED METAL FLASHING w/  
 DRIP EDGE SET ON TWO BEADS OF  
 URETHANE SEALANT

2% SLOPE MIN.

2" MIN.

BUILDING PAPER

AIR / VAPOR BARRIER

**Arriscraft**  
 Building Stone · Brick · Limestone

**ARRISCRAFT-CADD**

DETAIL No:

SSETB - DP2S

TITLE:

FOUNDATION TO WALL  
 JUNCTION WITH PAVING

**U001**

DATE DRAWN:  
 02 Mar 2022

SCALE:  
 3"=1'-0"

DRAWN BY:  
 TRI